



SIMOTION Drive-based Control Unit D425-2 DP/PN; programmable motion controller; BASIC performance; interfaces: 12 DI, 16 DI/DO, 4 DRIVE-CLiQ, 2 PROFIBUS, 3 PROFINET ports, 2 ethernet, 2 USB, 1 option slot; incl. dual fan / battery module and battery

Figure similar

product brand name	SIMOTION
product type designation	D425-2 DP/PN
Performance class for motion control system	BASIC Performance
Version of the motion control system	Multiple-axis system
PLC and motion control performance	
number of axes / maximum	16
Minimum PROFIBUS cycle clock	1 ms
Minimum PROFINET send cycle clock	0.25 ms
Minimum interpolator cycle clock	0.5 ms
Minimum servo cycle clock	0.5 ms
Integrated drive control / header	
Maximum number of axes for integrated drive control	
• servo	6
• vector	6
• V/f	12
• note	Alternative control modes; drive control based on SINAMICS S120 CU320-2, firmware version V4.x/V5.x
Memory	
RAM (work memory)	78 Mbyte
Additional RAM work memory for Java applications	20 Mbyte
RAM disk (load memory)	38 Mbyte
Retentive memory	364 kbyte
Persistent memory (user data on CF)	1.5 Gbyte
Communication	
Interfaces	
• DRIVE-CLiQ	4
• USB	2
• Industrial Ethernet	2
• PROFIBUS	2
— note	Equidistant and isochronous; Can be configured as master or slave
• PROFINET	1
— note	1 interface with 3 ports onboard; 1 interface with 4 ports optional via CBE30-2; functionality: supports PROFINET IO with IRT and RT; configurable as PROFINET IO Controller and/or Device; supports media redundancy (MRP and MRPD)
General technical data	
Fan	Double fan/battery module included in scope of delivery
DC supply voltage	
• rated value	24 V
• minimum	20.4 V

<ul style="list-style-type: none"> • maximum 	28.8 V
consumed current / typical	1 000 mA
<ul style="list-style-type: none"> • note 	with no load on inputs/outputs, no 24 V supply via DRIVE-CLiQ and PROFIBUS interface
Making current, typ.	5 A
Power loss, typ.	24 W
Ambient temperature, during	
<ul style="list-style-type: none"> • long-term storage • transport • operation — note 	-25 ... +55 °C -40 ... +70 °C 0 ... 55 °C Maximum installation altitude 4000 m (13124 ft) above sea level. Above an altitude of 2000 m (6562 ft), the maximum ambient temperature decreases by 7 °C (12.6 °F) per 1000 m (3281 ft).
Relative humidity	
<ul style="list-style-type: none"> • during operation • without condensation, tested acc. to IEC 60068-2-38 	5 ... 95 % Wert fehlt
Product property / Conformal coating	No
Resistance	
<ul style="list-style-type: none"> • to biologically active substances, / conformity acc. to EN 60721-3-3 • to chemically active substances, / conformity acc. to EN 60721-3-3 	No No
Air pressure	620 ... 1 060 hPa
Degree of protection	IP20 / UL open type
height	380 mm
width	50 mm
<ul style="list-style-type: none"> • depth • Depth / Note 	270 mm When the spacer is removed 230 mm (9.05 in) deep
net weight	3 700 g
Digital inputs / header	
number of digital inputs	12
DC input voltage	
<ul style="list-style-type: none"> • rated value • for signal "1" • for signal "0" 	24 V 15 ... 30 V -3 ... +5 V
Electrical isolation	Yes
<ul style="list-style-type: none"> • note 	Yes, in groups of 6
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	
<ul style="list-style-type: none"> • signal "0" → "1", typ. • signal "1" → "0", typ. 	50 µs 150 µs
Digital inputs/outputs / header	
Number of digital I/Os	16
Parameterization possibility of the digital I/Os	can be parameterized - as DI - as DO - as probe input (max. 16) - as cam output (max. 8)
If used as an input / header	
DC input voltage	
<ul style="list-style-type: none"> • rated value • for signal "1" • for signal "0" 	24 V 15 ... 30 V -3 ... +5 V
Electrical isolation	No
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	
<ul style="list-style-type: none"> • signal "0" → "1", typ. • signal "1" → "0", typ. 	5 µs 50 µs
Measuring input / reproducibility	5 µs
Measuring input / resolution	1 µs
If used as an output / header	
Load voltage	
<ul style="list-style-type: none"> • rated value • minimum 	24 V 20.4 V

<ul style="list-style-type: none"> • maximum 	28.8 V
Electrical isolation	No
Current carrying capacity for each output, max.	500 mA
Leakage current, max.	2 mA
Output delay for <ul style="list-style-type: none"> • signal "0" → "1", typ. • signal "0" → "1", max. • signal "1" → "0", typ. • signal "1" → "0", max. — note 	150 μs 400 μs 75 μs 150 μs Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut
Cam output <ul style="list-style-type: none"> • reproducibility • resolution 	10 μs 1 μs
Switching frequency of the outputs for <ul style="list-style-type: none"> • resistive load, max. • inductive load, max. • lamp load, max. 	4 kHz 2 Hz 11 Hz
Short-circuit protection	Yes
Additional technical data	
Back-up of non-volatile data <ul style="list-style-type: none"> • of retentive data • of real-time clock, min. • note 	unlimited buffer duration 4 d longer buffer duration of the real-time clock using a battery inserted in the double fan/battery module
Approvals <ul style="list-style-type: none"> • USA • Canada • Australia • Korea • Russia, Belarus and Kazakhstan 	cULus cULus RCM (formerly C-Tick) KCC EAC

