



Figure similar

MLFB-Ordering data

6SL3210-5FE11-0UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data		Ambient conditions	
<b>Input</b>		<b>Cooling</b>	natural convection
Number of phases	3 AC	<b>Installation altitude</b>	1000 m
Line voltage	380 ... 480 V +10 % -15 %	<b>Ambient temperature</b>	
Line frequency	45 ... 66 Hz	<b>Operation</b>	0 ... 45 °C
<b>Output</b>		<b>Storage</b>	-40 ... 70 °C
Rated power	1.00 kW	<b>Relative humidity</b>	
Rated current (IN)	3.00 A	<b>Max. operation</b>	90 %
Max. output current	9.00 A	<b>Standards</b>	
<b>Inputs / outputs</b>		<b>Compliance with standards</b>	CE, KC, cULus, EAC, C-Tick (RCM)
<b>Standard digital inputs</b>		<b>Communication</b>	
Number	10	<b>Communication</b>	USS, Modbus RTU
<b>Digital outputs</b>			
Number	6		
<b>Analog inputs</b>			
Number	2		
<b>Analog outputs</b>			
Number	2		
<b>Mechanical data</b>			
Degree of protection	IP20 / UL open type		
Frame size	FSA		
Net weight	1.85 kg		
Width	80.0 mm		
Height	180.0 mm		
Depth	200.0 mm		