



Summary

Request a quote

Catalog

Number of contacts Low Voltage	4
Wire Size/AWG	28 - 20
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	3.70 - 4.10 mm
Size	2C
Matching parts	ERA.2C.304.CLL

Technical details

Electrical Configuration

Contact Termination Low voltage	Solder
Insert configuration value	2C.304 - 4 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	15 Amps
Vtest	1800 V (AC), 2400 V (DC)
Contact Type	Solder
Bucket Dia.	1
Contact Dia.	1.3
Number of contacts Low Voltage	4
Wire Size/AWG	28 - 20

https://www.lemo.com/int_en/ffa-2c-304-clac42.html


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Form & Material

Shell style / Model id	FFA - Straight plug, cable collet
Plug	Straight
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	Hermaphroditic keying (half moon insert) with male pin 1
Weight	14.44 g
Environment	
Environmental protection (IP rating)	IP50
Salt Spray Corrosion	>1000 hr
Cable fixation	
Cable termination protection	Standard back nut (no additional protection)
Fixation type	Cable collet
Jacket cable outside diameter [mm]	3.70 - 4.10 mm

Drawings







Dimensions

	Α	L
mm.	14	30
in.	0.55	1.18

https://www.lemo.com/int_en/ffa-2c-304-clac42.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Recommended By Lemo

Accessories

Tools

Cables

Cable PartNumber	Material	Colour	Cable image
40086	PVC	Blue	
40140	PVC	Black	
40240	PTFE	White	≥€

https://www.lemo.com/int_en/ffa-2c-304-clac42.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.